



It's advanced formulation
and construction creates
an incredibly durable
hose at a great value.

ContiTech's new Plicord®
ExtremeFlex® Versiflow®
One Source, Many Solutions.



Plicord® ExtremeFlex® Versiflo

Premium Water Suction & Discharge Hose

APPLICATION: A light to medium general-purpose water suction and delivery hose, suitable for various industrial, agricultural and construction areas.

- › More Flexible: Easier to move in and out of tight spaces and around corners.
- › Lighter Weight: Easier to lift and carry, resulting in fewer workplace injuries.
- › Lower Force to Bend: Easier to connect and disconnect for increased productivity
- › Improved Flex Performance: More durable and longer lasting

TUBE: Black EPDM

REINFORCEMENT: Synthetic fabric with double wire helix

COVER: Corrugated Black EPDM

TEMPERATURE: -40°C to 93°C

BRANDING: Continental ContiTech Plicord® ExtremeFlex® Versiflo 150PSI WP Water S&D

SAP NO.	ID		NOM. OD	MAX. WP		BEND RADIUS		VACUUM HG		WEIGHT		COIL LENGTH
	in.	mm.		psi	Mpa	in.	mm.	in.	mm.	lb./ft.	kg/m.	
20893098	1	25.4	35.4	150	1.034	1	25.4	29	737	0.47	0.70	30.48
20893099	1¼	31.8	41.1	150	1.034	1¼	32.0	29	737	0.54	0.80	30.48
20893100	1½	38.1	47.4	150	1.034	1½	37.1	29	737	0.63	0.95	30.48
20893101	2	50.8	60.1	150	1.034	2	50.8	29	737	0.82	1.22	30.48
20893102	2½	63.5	75.1	150	1.034	2½	63.5	29	737	1.27	1.89	30.48
20893103	3	76.2	87.8	150	1.034	3	76.2	29	737	1.51	2.24	30.48
20893104	4	101.6	114.5	150	1.034	4	101.6	29	737	2.23	3.33	30.48

