

Industrial Hose

Gorilla® Air and Multipurpose Hose

Gorilla® Air and Multipurpose Hose Is A Beast!

Our premium-quality, multipurpose industrial hose is Continental's #1 selling product in this category for a reason. We use high-grade materials, innovations in design and engineering, and advanced production techniques to produce the most consistent industrial hose quality. Here's what Gorilla* delivers:

- > Superior abrasion resistance: Our Carbryn™ cover technology is a specially formulated carboxylated nitrile which helps it survive the toughest applications.
- **Less hose degradation:** Gorilla's cover is less porous than lesser quality hoses resulting in a hose that will stand up longer over time.
- **Diesel applications:** The new and improved nitrile tube compound withstands the adverse effects of diesel applications.
- **Versatility:** Gorilla's overall strength and durability allows for use in a wide range of applications and industries including agriculture, construction, manufacturing, mining, railroads, quarries, and the energy sector.

We Stand Behind Gorilla With Our Performance Warranty

Double Your Money Back If It Doesn't Outperform Your Current Hose.

We are so confident the Continental Gorilla* Air and Multipurpose Hose will outperform the hose you are using now that we will give you double your money back if it doesn't do the job. Simply let us know that you have a multipurpose hose test application where you want to try Gorilla*. Give us some details about your application, what brand and type you are currently using, and how much service life you have been getting.

We will deliver the required test length of Gorilla* and invoice you at the normal selling price. Gorilla* will outlast the multipurpose hose it replaced, or we will give you back double what you were invoiced. No catch. No strings.

No gimmicks. It is just our way of demonstrating that Gorilla* will perform to your satisfaction.

Our Performance Warranty is your assurance that Continental hose provides the best in class of any multipurpose hose in the industry. Don't take our word for it.

Try Gorilla hose at your operation and see for yourself.





GORILLA[®]



PERFORMANCE + SPECS

Tube Material

- > Nitrile (NBR)
- > ARPM Class A (High Oil Resistance)

Cover Material

-) Carbryn™
- > ARPM Class A (High Oil Resistance)
- > MSHA Approved

Reinforcement

- > Spiral Flexten Yarn
- > 2" is Braided Synthetic Yarn*

Temperature Range

> -20°F to 210°F (-29°C to 99°C)

Design Factor

) 4:1

Packaging

- > 3/16" to 3/4" 500 ft reels
-) 1" − 450 ft reels
-) 1-1/4" 250 ft to 400 ft reels
- > 1-1/2" 150 ft to 300 ft reels
- > 2" 200 ft reels*
- Max. 3 Pieces per reel, 50 ft increments

Coupling

Refer to the Continental Industrial Hose Assembly Manual for crimp specifications



KEY FEATURES



Coupled Assembly Available



High Oil Resistance Tube & Cover




Flame Resistance / MSHA Approved



Non-Conductive Tube & Cover



Superior Abrasion Resistant Cover



We recommend using the Vari-Crimp Fittings we have in-stock! Crimp specs available in our Industrial Hose Assembly Manual.

SAP	ID		OD OD		Max Working Pressure		(b) Weight		 Length
SAP Number									
	in	mm	in	mm	PSI	MPa	lbs/ft	kg/m	ft
20026239	1/4	6.40	0.61	15.50	500	3.45	0.17	0.25	500
20026255	5/16	7.94	0.69	17.50	500	3.45	0.20	0.30	500
20026256	3/8	9.53	0.73	18.60	500	3.45	0.22	0.33	500
20026273	1/2	12.70	0.89	22.60	500	3.45	0.28	0.42	500
20026289	5/8	15.88	1.06	26.90	500	3.45	0.35	0.52	500
20026290	3/4	19.10	1.19	30.20	500	3.45	0.41	0.61	500
20026304	1	25.40	1.50	37.80	500	3.45	0.58	0.86	450
20026306	1-1/4	31.80	1.77	45.60	500	3.45	0.79	1.18	400
20026309	1-1/2	38.10	1.77	51.80	500	3.45	0.86	1.27	300
20305356*	2	50.80	2.62	66.60	500	3.45	1.22	1.82	100
20023183*	2	50.80	2.62	66.60	500	3.45	1.22	1.82	50

*As of June 2023 the 2" hose is not recommended for diesel applications.



Continental

703 S. Cleveland Massillon Road Fairlawn, OH 44333-3023 U.S.A. 1-800-235-4632 www.continental-industry.com

Your local contact

www.contitech.de/contactlocator

Canada

1-888-275-4397

Mexico

1-800-439-7373

